

# TECHNICAL SPECIFICATIONS

## DR005 – UDR100 – KL 100 Heli Portable



### Carrier

Skid

### Build Date

2007

### Rig Dimensions

Base length:	2.20	m
Base width:	1.80	m
Height Mast Down:	1.79	m
Height Mast Up:	7.40	m
Weight:	2250	kg

### Standard Features

Usable Fuel Capacity:	80	l
Max Feed Force:	32	kN
Max Stroke:	6.00	m
Max Rod Pull:	7.50	m
Max Power:	73	Kw
Max Torque:	1300	Nm

### Maximum Practical Depth

HQ Drilling:	225	m
PQ Drilling:	75	m
NQ Drilling:	350	m

### Recirculating Pump

Stalker:	50	SHL
Pump Flow (L/Min):	227	lpm
Max Pump Pressure:	30	psi

### Water Pump

Main Pump:	FMC W1122	
Pump Flow (L/Min):	140	lpm
Max Pump Pressure:	1000	psi



### Features:

- Rod Guard
- Fire Extinguishers
- Emergency Shut Down System
- Safety Steps
- Lockable Battery Isolation Point



Free call 1800 082 200  
[www.hagstromdrilling.com.au](http://www.hagstromdrilling.com.au)