

TECHNICAL SPECIFICATIONS

DR022 – D&B 8-D DIAMOND DRILL RIG



Carrier

Track mounted D&B 8-D

Build Date

2016

Rig Dimensions

OA Length:	5.40	m
OA Width:	1.91	m
OA Transport Height	2.0	m
Height Mast Up:	6.40	m
Dry Weight:	4000	kg

Standard Specifications

Max. Pull-back:	8000	kg
Retract speed:	25	m/min
Pull Down Speed:	30	m/min
Working Table Dia	250	m/min
Engine Capacity	40	kW @ 1800 rpm
Max. Spindle Speed	850	rpm
Pump Output	200	lpm @ 30 bar
Main winch capacity	3000	kg
Pull Down	4000	kg
Stroke	3.5	m
Rod Pull	3.0	m
Head torque (max.)	3530	Nm
W/L Winch Capacity	500	m of 6mm

Maximum Practical Depth

Diamond Coring:	PQ	80	m
	HQ	150	m
	NQ	250	m
Rotary (100-150 mm dia.):		150	m
DHH(100-150 mm dia.):		150	m



Features:

- Wireless Remote Trimming
- Rubber tracks
- Dual motor rotation head
- Wireline winch
- Kioti diesel motor
- Top head drive
- 200 lpm variable volume mud pump
- Hydraulically operated rod basket
- Rod guard with interlock



Free call 1800 082 200
www.hagstromdrilling.com.au